



1	VSS	Power ground
2	VDD	Power supply (+5V)
3	V0	Contrast adjust
4	RS	Register select
5	R/W	H: Read, L: Write
6	E	Enable signal
7	DB0	DATA BUS 0
8	DB1	DATA BUS 1
9	DB2	DATA BUS 2
10	DB3	DATA BUS 3
11	DB4	DATA BUS 4
12	DB5	DATA BUS 5
13	DB6	DATA BUS 6
14	DB7	DATA BUS 7
15	A	Backlight (+) +5V
16	K	Backlight (-)

- NOTES:
1. DISPLAY TYPE: STN, YELLOW-GREEN
 2. POLARIZER TYPE: TRANSPARENT, POSITIVE
 3. VIEW DIRECTION: 6:00
 4. OPERATING TEMPERATURE: 0°C~+50°C
 5. STORAGE TEMPERATURE: -20°C~+70°C
 6. VDD: +5V
 7. DRIVE METHOD: 1/16DUTY, 1/5BIAS
 8. CONTROLLER: S6A0069
 9. BACKLIGHT TYPE: YELLOW-GREEN, BOTTOM
 10. BACKLIGHT SUPPLY VOLTAGE: +5.0V
 11. VOP: TBD

WAYING (HONGKONG) SHARES LIMITED		DESIGN:	MODEL NUMBER:	UNITS:	MM
		CHECK:	WYM1602G	VERSION:	A
APPROVE:			SHEET:	1 OF 1	
Unspecified tolerances are ±0.3			DATE:	2005-06-08	