



| | | |
|----|-----|--------------------|
| 1 | VSS | Power ground |
| 2 | VDD | Power supply (+5V) |
| 3 | VO | Contrast adjust |
| 4 | RS | Register select |
| 5 | R/W | H: Read; L: Write |
| 6 | E | Enable signal |
| 7 | DB0 | DATA BUS 0 |
| 8 | DB1 | DATA BUS 1 |
| 9 | DB2 | DATA BUS 2 |
| 10 | DB3 | DATA BUS 3 |
| 11 | DB4 | DATA BUS 4 |
| 12 | DB5 | DATA BUS 5 |
| 13 | DB6 | DATA BUS 6 |
| 14 | DB7 | DATA BUS 7 |

NOTES:

1. DISPLAY TYPE: STN, YELLOW-GREEN
2. POLARIZER TYPE: TRANSPARENT, POSITIVE
3. VIEW DIRECTION: 6:00
4. OPERATING TEMPERATURE: -20°C ~ +70°C
5. STORAGE TEMPERATURE: -30°C ~ +80°C
6. VDD: +5V
7. DRIVE METHOD: 1/16DUTY, 1/5BIAS
8. CONTROLLER: S6A0069
9. BACKLIGHT TYPE: YELLOW-GREEN, BOTTOM
10. BACKLIGHT SUPPLY VOLTAGE: +4.2V
11. VOP: TBD

 **WAYING (HONGKONG) SHARES LIMITED**

DESIGN: MODEL NUMBER: UNITS: MM

CHECK: WYM0802A VERSION: A

APPROVE: SHEET: 1 OF 1

Unspecified tolerances are ±0.3 DATE: 2005-06-08