



1	VSS	Power ground
2	VDD	Power supply (+3.3V)
3	V0	Contrast adjust
4	RS	Register select
5	R/W	H: Read; L: Write
6	E	Enable signal
7	DB0	DATA BUS 0
8	DB1	DATA BUS 1
9	DB2	DATA BUS 2
10	DB3	DATA BUS 3
11	DB4	DATA BUS 4
12	DB5	DATA BUS 5
13	DB6	DATA BUS 6
14	DB7	DATA BUS 7
15	/CS1	Chip select for IC1.L active
16	RES	Reset signal
17	NC	
18	NC	
19	K	Backlight (-)
20	A	Backlight (+) +5V

NOTES:

1. DISPLAY TYPE: STN,YELLOW-GREEN
2. POLARIZER TYPE: TRANSPARENT, POSITIVE
3. VIEW DIRECTION: 6:00
4. OPERATING TEMPERATURE: -20°C~+70°C
5. STORAGE TEMPERATURE: -30°C~+80°C
6. VDD: +3.3V
7. DRIVE METHOD: 1/64DUTY, 1/9BIAS
8. CONTROLLER: ST7525
9. BACKLIGHT TYPE: YELLOW-GREEN, SIDE
10. BACKLIGHT SUPPLY VOLTAGE: +5.0V
11. VOP: TBD

WAYING (HONGKONG) SHARES LIMITED

DESIGN: MODEL NUMBER: WYM19264K1 UNITS: MM

CHECK: VERSION: A

APPROVE: SHEET: 1 OF 1

Unspecified tolerances are ±0.3 DATE: 2012-06-03