



1	VDD	Power supply (+5V)
2	VSS	Power ground
3	VO	Contrast adjust
4	DB0	DATA BUS 0
5	DB1	DATA BUS 1
6	DB2	DATA BUS 2
7	DB3	DATA BUS 3
8	DB4	DATA BUS 4
9	DB5	DATA BUS 5
10	DB6	DATA BUS 6
11	DB7	DATA BUS 7
12	/CS1	Chip select for IC1.L active
13	/CS2	Chip select for IC2.L active
14	RST	Reset select
15	R/W	H: Read; L: Write
16	RS	Register select. HD:DATA; L:INSTRUCTION
17	E	Enable signal
18	VEE	Negative power output
19	A	Backlight (+) +5V
20	K	Backlight (-)

NOTES:

1. DISPLAY TYPE: STN, YELLOW-GREEN
2. POLARIZER TYPE: TRANSPARENT, POSITIVE
3. VIEW DIRECTION: 6:00
4. OPERATING TEMPERATURE: -20°C~+70°C
5. STORAGE TEMPERATURE: -30°C~+80°C
6. VDD: +5V
7. DRIVE METHOD: 1/64DUTY, 1/9BIAS
8. CONTROLLER: SBNO064 OR EQUIVALENT
9. BACKLIGHT TYPE: YELLOW-GREEN, SIDE
10. BACKLIGHT SUPPLY VOLTAGE: +5.0V
11. VOP: TBD

WAYING (HONGKONG) SHARES LIMITED		DESIGN:	MODEL NUMBER:	UNITS:	MM
		CHECK:	WYM12864E	VERSION:	A
APPROVE:			SHEET:	1 OF 1	
Unspecified tolerances are ±0.3			DATE:	2005-07-08	